

# TD22DX

## CONTROLLER

Storage Air Temperature adjustment -  
electronic thermostat  
alarm code

Defrost - (Hot gas) : Automatic & Manual

## COMPRESSOR

Model : CR2211L

Discharge : 110 cc / rev

Comp. oil : Diamond Freeze MA32 (350cc)

Safety Device : Discharge temp. sensor

## EVAPORATOR

Type : Copper Pipe , Aluminum Fin

Fan : Centrifugation, Directly connected to  
fan motor

Rpm : 2000

Fan motor : 70W x 1

**TD22DX**

Split type For low temperature (DX)

Refrigerating capacity Temperature inside the refrigeratory (External air temperature 35°C)

0°C : 2,560W(2,200kcal/h)  
-18°C : 1,570W(1,350kcal/h)  
-25°C : 1,160W(1,000kcal/h)

Evaporator

Condenser

Controller

Compressor CR2211L-A (For low temperature)

Evaporator thickness of 128mm and width of 927mm, best choice for 1.5~2 tons short body trucks.

R404A

## CONDENSER

Type : Parallel flow, Aluminum fin

Fan : Propeller fan, Directly connected  
to fan motor

Rpm : 2100

Fan motor : 75W x 1

Specifications			
MODEL	TD22/ 12V, 24V		
Refrigerant R404a	V-BELT		
Refrigeration Capacity	0°C	2650 W	2200 Kcal/hr
	-18°C	1570 W	1350 Kcal/hr
	-25°C	1160 W	1000 Kcal/hr
	Compressor	CR2211L-A-7	
Total weight of product	61kg		
Power consumption	18 amps / 9 amps		